



High End Interactive Technology
CLASS ROOMS | TRAINING ROOMS | BOARD ROOMS

LTK Series



Wireless



Finger Touch



Pen Touch



Tough Screen

Android 14 

www.onfocus-tech.com

Diagonal display size		65(inch) LTK65ADV100	75(inch) LTK75ADV100	86(inch) LTK86ADV100
Bezel color	Aluminum frame(Black color)	√	√	√
Panel type	Ultra HD Direct type LED	√	√	√
Active area (mm)		1428.48 (H) * 803.52 (V)	1649.66 * 927.93(V)	1895.04 * 1065.96(V)
Resolution	3840*2160 /60hz	√	√	√
Pixel Pitch		0.372mm x 0.372mm	0.429 mm x 0.429 mm	0.4935 mm x 0.4935 mm
Hardness Glass	Mohs-7 level	√	√	√
Glass Panel	Anti-Glare glass with zero bonding	√	√	√
Aspect Ratio	16:9	√	√	√
Contrast Ratio	1200:1 (type)	√	√	√
Brightness	350cd/m2	√	√	√
Viewing angle	178°	√	√	√
Lifespan	50,000 hours	√ Touch Type	√	√
Touch Technology	IR touch	√	√	√
Multi Touch	Max 40 points(Windows)	√	√	√
Multi Writing	Max 20 points(Windows)	√	√	√
Touch Precision	1 mm (over 90% Area)	√	√	√
Auto-Calibration	Yes	√	√	√
Anti-light	Yes	√	√	√
Minimum object size	2mm	√	√	√
Touch Response Time	First Point <2 ms, Continuation <8 ms	√	√	√
Supporting OS	Windows 7/8/10/11; Android; Mac; Linux; Chrome OS	√ Sound	√	√

		LTK65ADV100	LTK75ADV100	LTK86ADV100
Speakers	2	√	√	√
Front Speakers	15W*2	√	√	√
Front Ports	USB3.0 * 3 lines (Public for both Android & PC); Touch out	Front Side Connections	USB B type * 1 line; HDMI in 2.0 *	1 line ; USB-C *1 line
Front Keys	Power on/off; Signal source; Setting; EC	Bottom Side Connections	O; Home; Volume up down; Volume	
TF Card	1	√	√	√
HDMI OUT	1	√	√	√
LAN-Port IN	1 (RJ45, 100 Mbit/s)	√	√	√
SPDIF	1	√	√	√
Earphone/Line Out	1	√	√	√
HDMI IN	1	√	√	√
Touch USB(HDMI)	1	√	√	√
Android USB 2.0	1	√	√	√
Android USB 3.0	1	√	√	√
Windows OPS Slot	80-pins OPS slot	√	√	√
WiFi Standard	Wi-Fi 5(2.4G+5G)	√	√	√
Bluetooth version	5.0	√	√	√
Android Version	Android 14.0	√	√	√
Chip	GK6780V100	√	√	√
CPU	8*A55,1.8GHZ	√	√	√
GPU	Mali-G52 MP2(2EE)	√	√	√
Memory	8GB DDR4	√	√	√
Storage	128GB	√	√	√
Compliant with	Windows; Mac; Linux; Chrome OS	√	√	√
Over-the-Air Updates (OTA)	YES	√	√	√

		LTK65ADV100	LTK75ADV100	LTK86ADV100
Light Sensor	option	√	√	√
		General Information		
Power Supply	~ 100-240 V (50/60Hz)	√	√	√
Switch On / Off	Yes	√	√	√
Standby Energy Consumption	≤ 0.5 Watt	√	√	√
Power Consumption		Maximun< 290W Eco<75W	Maximun< 420W Eco<75W	Maximun< 530W Eco<75W
Net Weight	(KG±2)	40	51	65
Gross Weight	(KG±2)	50	63	80
Screen Dimensions	(WxDxH)	1470.9 * 97.5 * 897.5 mm	1692.1 * 97.5 * 1021.9 mm	1943.4 * 97.5 * 1166 mm
Dimensions Package	(WxDxH)	1594*1005*170mm	1818*1120*165 mm	2055*1272*168 mm
VESA Standard	(mm)	600*400 mm	600*400 mm	800*600 mm
Certifications	Ce.FCC.Rosh	√	√	√
Warranty	ONE year for the whole product and THREE years for touch parts by default. (can be extended, it's for an option)	√	√	√
		Environmental conditions		
Operating Temperature	0°C - 38°C/32 - 100 °F	√	√	√
Storage Temperature	-10°C - 60°C/-4 - 140 °F	√	√	√
Storage Humidity	10 % - 60 %	√	√	√
Usage Humidity	20 % - 85 %	√	√	√
		Accessories		
Accessories	WIFI antenna*4pcs, No ink pen * 2pcs, Remote control *1pc, 1.5m power cord *1pc, 1.5m HDMI cable *1pc, 1.5m USB touch cable *1pc; wall mount kit			